



Their Upgrades  
Our  
**STANDARDS**



MODELS LC290 | LC390 | LC535 | 2-50 | 4-50 | C4-50





## Their Upgrades Our **STANDARDS**

The SpeedTender Seed Delivery System by J&M has become the best seed tender on the market by helping farmers increase their planting efficiency. The extra-long conveyor can quickly and gently dispense seed to the widest and tallest planters, then rotate 180 degrees for easy self-filling. A patented V-Belt and skirting design keeps the belt centered, reducing seed damage and the chance of premature wear due to misalignment. The larger tank opening makes it easy to completely refill, while keeping the center of gravity low for greater stability. The LC290, 390 and 535 tenders all have a halogen work light on the tank and conveyor for night time unloading. Optional scales and luxury controls allow you to customize the tender to fit your precise planting operation, saving time and money.

### LC Series SpeedTenders™

The LC Series Speed Tenders offer improved features to maximize your planting efficiency. The improved tank and patented support arm design features a large capacity tank with lower overall height, allowing you to carry more seed with a lower center of gravity while also making it easier to fill and more stable to transport over uneven terrain.

The longer conveyor with large diameter round tube belt design makes it easy to reach the tallest central fill and widest box row planters. Our patented Tru-Trak with V-Belt conveyor is designed to reduce seed damage and premature wear on the conveyor belt due to misalignment.

J&M SpeedTenders are designed to make your planting season EFFICIENT AND EASY. That is why we've included many of the competitor's upgrades into our standard models. Don't be fooled by their lower prices, as it's probably not an "apples to apples" comparison.





## LC - Lower Center of Gravity

The LC Series has been designed with a lower overall height and a lower center of gravity, making filling easier and transport more stable, even over uneven terrain.

## LC - Larger Capacity

The LC SpeedTender's™ larger capacity allows you to transport more seed and keeps you on the go during the busy planting season.

**Speedtender**  
ADVANCED SEED DELIVERY



## LC - Luxury Controls

A) Standard All-Function Remote  
Starts/Stops Conveyor  
Raises/Lowers Conveyor  
Opens/Closes Tank Doors  
Hydraulically Swings Conveyor



B) Optional Deluxe Wireless Remote  
Starts/Stops Conveyor  
Raises/Lowers Conveyor  
Opens/Closes Tank Doors  
Hydraulically Swings Conveyor  
Electronic Scale Shut-Off



C) WC3-D SpeedTender Scale & Wireless Control System

Scale Indicator  
Wireless Remote  
Wireless Receiver  
On-Board Controller  
Auto Dispense  
Load Cells  
Conveyor Speed  
Talc Speed  
Engine Controls



**LCseries**

Variable Speed Control

Available On Both Standard And Upgrade Controls

Optional Dual Wheel LC390



An optional tandem axle undercarriage design (390ST-2AS) is available for Model LC390 and features a heavier torsion axle, wheels and tires for greater maneuverability and easier towing.

## LC - Longer Conveyor

The X-tra Long Conveyor offers greater reach and height to service the tallest and widest planters. A patented V-Belt and skirting design keeps the belt centered, reducing seed damage and chance of premature wear due to misalignment. The new skirting design also reduces the potential of damaging seed and collecting debris. Competitor conveyor designs feature crowned rollers that allow the belt to "walk" back and forth, making it difficult to maintain alignment and prevent premature wear.



V-Guided Belt

**TrueTrak**  
V-Belt

No Hassle Alignment



## Standard Features - Model c4•50

- 22' X-tra Long 8" Conveyor
- On-Board Controller
- Patented Tru-Trak V-Belt For No Hassle Alignment and Less Maintenance
- Attached Metal Weather Tight Lids
- 13 HP Honda Engine
- Convenient Open Engine Placement
- Easy-To-Use Locking Container Latches
- Trouble Free Guide Plates For Easy Loading

## Available Options



- Choice of Durable Red, Green, Blue and Tan Urethane Exterior Finish
- Choice of Standard Wire Remote or Deluxe Wireless Remote
- Choice of A-Frame, Gooseneck or Trailer Mount
- 2-Stage Telescoping Spout
- Optional Hydraulic Jack
- Electronic Weigh System (Weights Seed From Tank For Empty Conveyor)
- Talc Applicator
- Working Lights for Night Time Unloading
- Divided Hopper For Quick and Easy Variety Changes



## Standard Features - Models 2•50 | 4•50

- Auger Height (16'-9")
- 19 ft 3-Stage Telescoping Spout
- Poly-Cupped Plastic Auger Flighting
- Reversible Auger Switch For Complete Cleanout
- Low Deck Height (4'-2")
- 41 Degree Chute Angle
- Two (2) 7,000 lbs Torsion Flex Axles (4•50 Models)
- Two (2) 5,200 lbs Torsion Flex Axles (2•50 Models)
- 13 HP Honda Engine
- 4 Minute Per Box Flow Rate
- Heavy Tubular Frame
- Powder Coated Exterior Finish
- Easy Access Cleanout Door
- Trouble Free Guide Plates
- Work Light For Night Time Unloading

## Available Options



- Choice of Durable Red, Green, Blue and Tan Powder Coat Finish
- Choice of Standard or Wireless Controls
- Choice of A-Frame, Gooseneck or Trailer Mount
- Electronic Weigh System (Weights Seed From Tank For Empty Auger Tube)
- 24 ft 3-Stage Telescoping Spout
- Talc Applicator







## Standard & Optional Controls

### Model C4•50

#### A) Standard All-Function Remote

Starts/Stops Conveyor  
Raises/Lowers Conveyor  
Opens/Closes Tank Doors  
Hydraulically Swings Conveyor



#### B) Optional Deluxe Wireless Remote

Starts/Stops Conveyor  
Raises/Lowers Conveyor  
Opens/Closes Tank Doors  
Hydraulically Swings Conveyor  
Electronic Scale Shut-Off

### C) WC3-D SpeedTender Scale & Wireless Control System

Scale Indicator	Load Cells
Wireless Remote	Conveyor Speed
Wireless Receiver	Talc Speed
On-Board Controller	Engine Controls
Auto Dispense	



C

### Model Pro 2•50 & 4•50

#### A) Standard All-Function Remote

Starts/Stops Auger  
Raises/Lowers Auger



#### B) Optional Deluxe Wireless Remote

Starts/Stops Auger  
Raises/Lowers Auger

## Variable Speed Control

Available On Both Standard And Upgrade Controls





Seed Tender  
Dimensions

LC290 | LC390 | LC535

	LC290	LC390	LC535
A	5'-1" (A-Frame)	4'-9" (A-Frame)	-----
A	2'-10" (Gooseneck)	2'-8" (Gooseneck)	3'-6" (Gooseneck)
B	1'-6" (min) (A-Frame)	1'-6" (min) (A-Frame)	-----
B	2'-7" (min) (Gooseneck)	2'-7" (min) (Gooseneck)	2'-9" (min) (Gooseneck)
B	1'-10" (max) (A-Frame)	1'-10" (max) (A-Frame)	-----
B	3'-3" (max) (Gooseneck)	3'-3" (max) (Gooseneck)	3'-4" (max) (Gooseneck)
C	21'-3" (A-Frame)	22'-1" (A-Frame)	-----
C	23'-5" (Gooseneck)	24'-4" (Gooseneck)	29'-2" (Gooseneck)
D	9'-3"	9'-8"	10'-8"
E	3'-10"	3'-10"	4'-0"
F	17'-11"	17'-11"	20'-2"
G	8'-6"	8'-6"	8'-6"
H	16'-4" (max)	16'-4" (max)	17'-0" (max)
H	8'-7" (min)	8'-7" (min)	8'-7" (min)
I	17'-4" (max)	17'-4" (max)	20'-4" (max)
I	12'-10" (min)	12'-10" (min)	16'-2" (min)
J	9'-9"	10'-2"	11'-5"
K	11'-0"	11'-0"	11'-0"

c4-50

	A-Frame	Gooseneck	Trailer Mount
A	4'-10"	2'-10"	12'-9"
B	1'-6" (min)	2'-7" (min)	NA
B	1'-10" (max)	3'-3" (max)	NA
C	20'-4"	22'-6"	12'-5"
D	11'-3"	11'-3"	10'-8"
E	8'-6"	8'-6"	8'-6"
F	14'-2" (max)	14'-2" (max)	14'-2" (max)
F	8'-7" (min)	8'-7" (min)	8'-7" (min)
G	16'-5" (max)	16'-5" (max)	16'-5" (max)
G	13'-7" (min)	13'-7" (min)	13'-7" (min)

2-50 | 4-50

	Pro 2-50	Pro 4-50
A	16' 9"	16' 9"
B	20'	20'
C	4' 10"	4' 10"
D	4' 2"	4' 2"
E	8' 4"	8' 4"
F	9' 3"	9' 3"
G	11' 0"	11' 0"
H	13' 6"	16' 5"



Seed Tender  
Specifications

	Capacity (total)**	Weight (empty)	Tongue Wt. (loaded)	Conveyor/Auger	Unloading Rate	Conveyor/Auger Reach	Axles	Engine
LC290	290 Seed Units 290 Cubic Feet	6,100 lbs.	1,650 lbs. 1,207 lbs. (Gooseneck)	22' Long, 8" Tube Conveyor	30 Bushels/Min	49' (front to rear swing)	Two (2), 7,000 lb. Torsion-Flex Axles w/Electric Brakes	13 HP Honda Motor w/Electric Start
LC390	390 Seed Units 390 Cubic Feet	7,500 lbs.	1,380 lbs. 1,453 lbs. (Gooseneck)	22' Long, 8" Tube Conveyor	30 Bushels/Min	49' (front to rear swing)	Three (3), 7,000 lb. Torsion-Flex Axles w/Electric Brakes	13 HP Honda Motor w/Electric Start
LC390ST-2AS							Two (2), 10,000 lb. Axles w/Electric Brakes	
LC535	535 Seed Units 535 Cubic Feet	11,000 lbs.	4,900 lbs.	24.5' Long, 10" Tube Conveyor	45 Bushels/Min	50' (front to rear swing) (w/telescoping spout)	Two (2), 16,000 lb. Dual Wheel, Spring Ride w/Electric Brakes	13 HP Honda Motor w/Electric Start
Pro C4-50	Four (4), 50 Unit Boxes	6,300 lbs.	1,650 lbs.	22' Long, 8" Tube Conveyor	30 Bushels/Min	49' (front to rear swing)	Two (2), 7,000 lb. Torsion-Flex Axles w/Electric Brakes	13 HP Honda Motor w/Electric Start
Pro 2-50	Two (2), 50 Unit Boxes	3,800 lbs.	580 lbs.	16' Spout Height	4-Minutes per Box	42' (w/optional 24' spout)	Two (2), 5,200 lb. Torsion-Flex Axles w/Electric Brakes	13 HP Honda Motor w/Electric Start
Pro 4-50	Four (4), 50 Unit Boxes	5,200 lbs.	1,600 lbs.	16' Spout Height	4-Minutes per Box	42' (w/optional 24' spout)	Two (2), 7,000 lb. Torsion-Flex Axles w/Electric Brakes	13 HP Honda Motor w/Electric Start





\*Specifications and dimensions are subject to change without notice or obligation.

\*\*Measured with soybeans at 140,000 seeds per unit weighing 45 lbs.







J&M Manufacturing  
Premium Seed Tenders




MODEL LC290






MODEL LC390






MODEL LC535



MODEL C4-50



MODEL 4-50 | 2-50







### Standard

#### On-Board Controller

The On-Board Controller is a secondary control option for both the standard wired and optional wireless units in case the batteries fail, the remote is misplaced or a cord is damaged. The On-Board Controller can be used in conjunction with the current controls, allowing the operator to switch back and forth seamlessly, and has the optional Talc Applicator controls included.



### J&M Talc Applicator

NEW DESIGN



### GUARANTEE

J & M MANUFACTURING CO guarantees against any faulty construction or materials for a period of ONE year. We reserve the right to inspect and decide whether material or construction was faulty or whether abuse or accident voids our guarantee.

Specifications are subject to change without notice or obligation.  
® Registered Trademark of J&M Mfg., Co. Inc.



73747 130TH ST  
ZEARING IA 50276  
641-487-7608  
INFO@NESSAINC.COM  
WWW.NESSAINC.COM

